

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
15 September 2005 (15.09.2005)

PCT

(10) International Publication Number
WO 2005/084806 A1

(51) International Patent Classification⁷: **B01J 37/02**,
35/04, B01D 46/24, 53/94, B05D 3/04, 7/22

Vincent [GB/GB]; 108 Ermine Street, Caxton, Cambridge
CB3 8PQ (GB).

(21) International Application Number:
PCT/GB2005/000870

(74) Agent: NUNN, Andrew, Dominic; Johnson Matthey
Technology Centre, Blounts Court, Sonning Common,
Reading RG4 9NH (GB).

(22) International Filing Date: 7 March 2005 (07.03.2005)

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,
ZM, ZW.

(25) Filing Language: English
(26) Publication Language: English
(30) Priority Data:
0405015.9 5 March 2004 (05.03.2004) GB


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

(71) Applicant (for all designated States except US): JOHN-
SON MATTHEY PUBLIC LIMITED COMPANY
[GB/GB]; 2-4 Cockspur Street, Trafalgar Square, London
SW1Y 5BQ (GB).

(72) Inventor; and
(75) Inventor/Applicant (for US only): TWIGG, Martyn,

[Continued on next page]

(54) Title: METHOD OF MANUFACTURING A CATALYSED CERAMIC WALL-FLOW FILTER



(57) Abstract: A method of manufacturing a catalysed ceramic wall-flow filter comprising a plurality of channels comprises reducing the pressure in a pore structure of the channel walls relative to the surrounding atmospheric pressure, contacting a surface of the evacuated channel walls with a liquid containing at least one catalyst component or a precursor thereof, whereby the liquid permeates the evacuated channel walls, and drying and calcining the filter containing the catalyst component or its precursor. An apparatus (100) for use in the method comprises means (120) for sealingly isolating a plurality of channels of a ceramic wall-flow filter (14) from the surrounding atmosphere, means (160, 200, 220) for reducing the pressure in the isolated channels to below the surrounding atmospheric pressure thereby to establish a vacuum in the pore structure of the filter walls, at least one reservoir (260) for holding a liquid containing at least one catalyst component or a precursor thereof and means (310, 300, 220) for dosing the isolated and evacuated channels with a pre-determined quantity of the liquid.

WO 2005/084806 A1



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*